Tennant SentineITM

Adjust your expectations. Tennant's Sentinel™ street sweeper from Tennant with a cleaning path up to 320cm is everything you need in a power sweeper; a sweeper with millions of hours of real world experience, Sentinel™ is the ideal combination of manoeuvrability, speed, performance and size. And with the proven drydust control for all-season operation, experience what it will do for the appearance of your site, community and the environment. It's simply the perfect tool to your cleaning program.



Features

- 2 High-volume vacuum fans
- Large capacity synthetic-singed polyester filter
- Roomy, quiet cab with heater-pressuriser and luxury spring-suspension seat
- Stainless steel hopper
- Touch panel control
- 4-Wheel steering and tight turning radius
- Variable high-dump
- Easy engine access

Benefits

- Excellent performance
- Effectively prevents dust exhaust
- Ensures operator comfort
- Very robust and can hold up to 2.6 m³ of debris
- All sweeping functions within easy reach for ease of use
- Gives the machine impressive manoeuvrability
- Allows for discharge into large roll-offs & dump trucks
- Easy to service & maintain

Applications

- Industrial facilities (cement and aluminium factories)
- Municipalities

- Parks
- · Parking areas



All sweeping functions within easy reach



Variable high-dump



Vacuum wand extends cleaning reach



Machine in action



TECHNICAL SPECIFICATIONS SENTINEL™

Machine Dimensions		
Working width (single side brush) Working width (dual side brushes) Working width (dual side brushes + vario sweep) Dimensions (lxwxh) Machine weight, nett	cm cm cm cm kg	175 221 320 445x178x254 6913
Cleaning System		
Area coverage - theoretical (max) Area coverage - practical (max) Length cylindrical brush x dia	m²/h m²/h cm	70,000 26,250 130 x 61
Sweeping System		
Airflow Water lift Hopper capacity, volume Hopper capacity, weight Hopper dump height	L/s kPa L kg cm	755 12.5 2600 3175/1850 (HD) 102/290 (HD)
Power		
Power source Total power consumption Protection class Sound level (DIN45635)	W MI/III dB(A)	diesel 6200/9500 III 78
Propelling		
Transport speed Working speed Climbing capacity Turning circle	km/h km/h % cm	40 15 20 396

Sentinel™

Configuration

- \bullet Sentinel $^{\text{TM}}$ street sweeper dry dust system
- Sentinel™ street sweeper wet dust system
- Sentinel™ street sweeper wet & dry dust system

The above mentioned configurations includes as standard a main and a side brush.

Accessories

• Brushes

Options

- Air conditioner Approval for licence plate Rubber rear bumpers (2) Fuel cap with filter Central greasing system
- Caterpillar turbo engine High dump with overload indicator High pressure spray Rotating light on cabin
- Lights on cabin and hopper Radio & tapedeck Passenger suspension seat Side brush unit left (dry)
- Side brush unit left (wet) Front & rear foam filled tyre & wheel Front & rear pneumatic tyre & wheel
- Sludge tool for removal/hopper clean out Vacuum wand Vario sweep system

Warranty conditions

24 Months (or max 2000 running hours) on parts and 12 months (or max 1000 running hours) on labour, whichever comes first, excluding wear items.



TENNANT NV

Industrielaan 6, 5405 AB Uden P.O. Box 6, 5400 AA Uden THE NETHERLANDS Tel: 00800-2255 8366 Fax: 00800-3298 3662 E-mail: europe@tennantco.com www.tennant-europe.com

TENNANT UK LTD.

Gladstone Road Northhampton NN5 7RX UNITED KINGDOM Tel: 00800-2255 8366 Fax: 00800-3298 3662 Tel: 01604 583191 (local rate UK only) Fax: 01604 587909 (local rate UK only) E-mail: europe@tennantco.com

995750-03/06

