



REINVENT HOW THE WORLD CLEANS

# T191

## Small walk-behind scrubber-dryer

### Simple to Use for Hard-to-Reach Areas

T191 is a small, maneuverable and reliable scrubber-dryer that provides effective cleaning with easy-to-use controls. Its large tank capacity in a small size machine and robust components enables high productivity. The T191 is ideal for cleaning small, narrow areas found in retail stores, cafeterias and offices.



### Simple to Use

Clean narrow and hard-to-reach areas easily with small size, ergonomic handle and maneuverable design.



### Productivity in a Small Size

Achieve more cleaning productivity compared to compact machines, with a large tank capacity and wide scrub path.



### Compact Storage

Easy to store with small size footprint and handle that folds down easily.

# Inside the T191

- 1. Reduce fatigue** for the operator with an adjustable handle and comfortable grip for easy machine use.
- 2. 3-stage vacuum motor** for high performance water recovery.
- 3. Easy-to-remove recovery tank** for quick cleaning and battery access.
- 4. High cleaning productivity** with large tank capacities and long run-times.
- 5. Excellent drying and consistent water pick-up** with the parabolic squeegee shape and position.
- 6. Simplify operator training** with preventative daily maintenance with yellow touch points.



## T191 Specifications

FEATURE	SPECIFICATION	
	PAD ASSIST	CORDED
Cleaning path		455 mm
Productivity (per hour) theoretical max		1631 m <sup>2</sup> /hr
Estimated coverage (per hour)*		1187 m <sup>2</sup> /hr
Scrubbing speed		3.5 kmh
Brush/pad speed		140 rpm
Brush/pad pressure		21 kg
Solution tank capacity		28 L
Recovery tank capacity		30 L
Battery run time - up-to hours**	2.5	-
Battery voltage	24V (2x12)	-
Dimensions - L x W x H (handle in upright position)		960 x 550 x 1220 mm
Dimensions - L x W x H (storage position with handle folded down)		960 x 550 x 718 mm
Squeegee width		550 mm
Weight (with heaviest battery)	93 kg	48 kg
Sound level (operator's ear)***	69 dB	80 dB

Specifications subject to change without notice.

\* Estimated coverage rates use the practical speed and empty/fill time standards from the 2004 ISSA Cleaning Times handbook.

\*\* Run times are based on Continuous Scrubbing Run Times.

\*\*\* Sound levels per ISO 11201 as recommended by the American Association of Cleaning Equipment Manufacturers & OSHA

For a demonstration or additional information, call **+32 3 217 94 11** or email **europe@tennantco.com**

**TENNANT EUROPE NV**  
tennant.eu